

# RS-232/422/485 TO Ethernet Converter

## E-P132 SPEC

### FUNCTION

- RS-232/422/485 TO Ethernet Converter
- Digital TTL I/O Controlled Via Ethernet

### SPEC

- CPU : 8-bit W78E58 , 40 MHz
- RAM : 32 KBytes ROM :32 KBytes
- Ethernet
  - ◇ Port : RJ-45 Connector
  - ◇ Speed : 10 Mbps
  - ◇ Protocol : ARP, IP, ICMP, UDP, TCP, HTTP, DHCP
  - ◇ Mode : TCP Server/Client ; UDP Client : Broadcast
  - ◇ Setup : HTTP Browser Setup (IE & Netscape)
  - ◇ Security : Setup Password & Connect Password
- Serial Port
  - ◇ Port : RS232 / 422 / 485 \* 1-Port
  - ◇ Speed : 300bps~115.2kbps
  - ◇ Parity : None, Odd, Even
  - ◇ Data Bit : 7, 8
  - ◇ Stop Bit : 1 , 2
  - ◇ RS-232 Pins : RX , TX , GND , RTS , CTS , DTR , DSR , DCD
  - ◇ RS-422 : Rx+ , Rx- , Tx+ , Tx-
  - ◇ RS-485 : Data+ , Data-
- Digital I/O Port
  - TTL Digital I/O \* 8
- Watch Dog Function
- Firmware On-lined Updated Via Ethernet
- Power : DC 9 V , 500mA
- Led-Lamp : SYS(PWR) , LAN , LAN Rx , LAN Tx,
- Environment : Operating Temp: 0°C ~50°C Storage Temp : -10°C ~70°C
- Dimensions : 110 \* 68 \* 26 mm ( W \* D \* H )
- WEIGHT : 140 gm

