

TM-T88III

Thermal Printer

EPSON®



- Fast and smooth
- Easy paper handling
- Easy maintenance and high reliability
- Versatile printing
- Speedy transactions

High-speed thermal printer

Drop-in

High-speed

Restaurant & Bar
Snow2

Phone : 888-88-8888
July 23, 2001


White Wine	\$8.40
Cocktail A	\$5.50
Cocktail B	\$5.50
Seafood Salad	\$15.50
Cheese	\$10.00
Fried Chicken	\$12.00

Fast and smooth

Issue receipts fast and smooth thanks to a printing speed of 150 mm/second.(Max.)

Easy paper handling

Paper loading is easy and trouble free. When you run out of paper, simply drop in a new roll. And an autocutter is included for clean receipt cutting.



Easy maintenance and high reliability

With an MCBF of 52 million lines, the TM-T88III boasts outstanding durability. This, combined with an easy-to-clean head and almost trouble-free maintenance, helps reduce maintenance costs.

Versatile printing

Page mode provides extra layout freedom. Smooth and scalable characters (enlargeable up to 64 times), landscaping and black-white reversal give coupons extra impact and improve the image of your establishment. Bar codes can be printed both vertically (ladder bar code) and horizontally (fence bar code).

Print Sample




Speedy transactions

To speed up transactions, up to 256 KB of flash memory for digital logos is available on the printer side.



APPEARANCE



SPECIFICATIONS

Print Method	Thermal line printing
Print Font	9 x 17 / 12 x 24
Column capacity	56 / 42 columns
Character size	0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H) mm
Character set	95 Alphanumeric, 37 International, 128 x 8 Graphic Traditional / Simplified Chinese, Thai, Japanese, Korean
	Bar code: UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE 39, CODE 93, CODE 128, ITF, CODABAR
Characters Per Inch	20 cpi / 15 cpi
Print Speed (Max.)	150 mm / sec. (47 lps, 1/8" conversion)
Data Buffer	4 KB or 45 bytes
Interface*	RS-232, Bi-directional parallel, RS-485, USB, 10 Base-T I/F
Paper Dimensions	Roll paper: 79.5 ± 0.5 (W) x dia. (Max.) 83.0 mm
Paper Thickness	0.06 to 0.07 mm
Power	24 VDC ± 7%
Power Consumption	Approx. 1.8 A (mean)
D.K.D.Function	2 drivers
Reliability MTBF	36 x 10 ⁴ hours
MCBF	52 x 10 ⁶ lines
Overall Dimensions	145 (W) x 195 (D) x 148 (H) mm
Mass	Approx. 1.8 kg
EMC Standards	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Safety Standards	UL, CSA, TÜV (EN60950)

*Dealer option: RS-485, USB, 10Base-T I/F
Please contact your EPSON representative.

OPTIONS



- PS-170 - Power supply unit
- PS-180 - Power supply unit
- WH-10 - Wall Hanging Bracket

ESC/POS® Proprietary Command System

EPSON took the initiative by introducing ESC/POS, a proprietary POS printer command system including patented commands and enabling versatile POS system construction with high scalability. Compatible with all types of EPSON POS printers and displays, this proprietary control system also offers the flexibility to easily make future upgrades. Its popularity is worldwide.

OLE POS

Taking the lead worldwide, EPSON offers OCX driver software for application development support in Windows® 95/NT environments.



Conforms to OLE POS specifications.

All features and specifications described are subject to change without notice. EPSON and ESC/POS are registered trademarks of SEIKO EPSON Corporation. Windows and Windows NT are registered trademarks of Microsoft Corporation in the United States and/or other countries. Company and product names are trademarks or registered trademarks of their respective companies.

Specifications are subject to change without notice.

SEIKO EPSON CORPORATION

For details, please contact:



This publication uses 35% recycled paper.

OS30240 0104A Printed in Japan