

9-pin, serial dot

TM-U675



Fast & Super Quiet

Throughput is fast thanks to bi-directional minimum distance printing.

Quieter than other impact dot matrix printers of its class.

Handy Features

ASB (Automatic Status Back) function automatically transmits changes in printer status.

Also offers the convenience of two-way paper loading.

High-Performance, Multi-Purpose Printer

Print method	9-pin serial impact dot matrix
Print font	Font 5 x 9 / 7 x 9
Column capacity (columns)	Receipt: 37 / 50, Slip / Validation: 45 / 60
Character size (mm)	1.56 (W) x 3.1 (H) / 1.24 (W) x 3.1 (H)
Character set	95 Alphanumeric, 37 International, 128 x 12 Graphic
Characters per inch	13.3 cpi / 17.8 cpi
Interfaces	RS-232, Bi-directional parallel, Dealer option: RS-485, USB, 10 Base-T I/F
Data buffer	4 KB or 45 bytes
Print speed	Approx. 5.14 lps (at 40 columns, 17.8 cpi)
Paper	Dimensions (mm) Roll paper: 82.5 ± 0.5 (W) x dia. 83.0 Slip: 70 (W) x 150 (L) to 148 (W) x 297 (L) Validation: 148 (W) x 70 (L) to 150 (W) x 210 (L)
Thickness (mm)	Roll paper: 0.06 to 0.085 / sheet Slip: 0.09 to 0.2 (total thickness: 0.09 to 0.31)
Copy capability	One original and two copies
Inked ribbon	ERC-32 (Purple, Black)
Ribbon life	Purple: 6 x 10 ⁶ characters, Black: 4 x 10 ⁶ characters
Power	24 VDC ± 10%
Power consumption	Approx. 1.8 A (mean)
D.K.D.function	2 drivers
Reliability	MTBF: 18 x 10 ⁴ hours MCBF: 37 x 10 ⁶ lines
Overall dimensions (mm)	186 (W) x 298 (D) x 195 (H)
Mass (Approx.)	5.8 kg
EMI standards	VCCI class A, FCC class A, CE marking, AS / NZS 3548 class B
Power supply	PS-170 (option)
Factory options	MICR device, Autocutter
Safety standards	UL / CSA / TÜV (EN60950)

